

BARCODE READER SAT LD101RF PLUS

FEATURES

- ✓ Plug and play, Connect and Scan.
- ✓ High scanning speed.
- ✓ Robust decoding engine with seamless 1D barcode analysis.
- ✓ Compact and sleek design.

DESCRIPTION:

The LD101RF PLUS scanner is ideal for any type of business, offering significant advantages as an affordable and feature-rich solution.

Designed with IP65 rating and a scanning speed of 300 scans per second, ensuring durability and efficiency.

This device delivers exceptional value for customers seeking high performance and cost-effectiveness in a sleek, comprehensive product. The package includes a resting base, USB cable, and a trigger for paused code reading.



MARKET AND APPLICATIONS

RESTAURANTS

::

HOSPITALS











MALLS

200

Ň

CINEMAS

SUPERMARKETS









:::



FASHION

AMUSEMENT PARK LOGISTICS

*Specifications are subject to change without notice.

SPECIFICATIONS

DESCRIPTION

Light Source	850mm laser (safe visible laser diode).
Decoding Capability	1D
Decoding capability	EAN-8, EAN-13, UPC-E, CODE39, CODE128, Codabar, Industrial 2 of 5, Interleaved 2 of 5, Matrix 2 of 5, MSI, China Post Code, and all standard 1D barcodes.
Scan Type	Linear laser.
Scan Speed	300 scans per second.
Scan Method	Automatic, Manual and continuous.
Scan Angle	Skew 65°, tilt 55°, rotation 65°.
Precision	3-4 mil (11.1mm).
Scan Depth	0–280mm (0.33mm, 80% PCS).
Error Rate	Less than 1 in 1,000,000.
Alerts	- LED indicator (correct function) - Audible indicator (correct tone function).
Interface	USB-HID.
Environmental Parameters	
Operating Temperature	0°C to 70°C
Storage Temperature	-40°C to 70°C
Relative Humidity	5% to 85% (non-condensing)
Drop Resistance	Withstands multiple drops onto concrete from up to 3m height.
Physical Parameters	
Dimensions	172mm x 83mm x 70mm.
Weight	200g
Material	ABS + PC
Cable Length	1.8m
Color	Black
Electrical Parameters	
Voltage	DC 5V
Power Consumption	85mA (operating).

CERTIFICATIONS:





SAT LD101RF PLUS



Other code readers:

Complementary products:

