SAT

BARCODE SCANNER

SAT LI102

FEATURES

✓ Linear 1D imager scanner

✓ Ability to read low-quality codes.

✓ Scans over screen

✓ Ideal equipment for any operating system.

✓ Reads any standard barcode type.

✓ Fast and easy to install.

✓ High reading speed.

✓ Resists multiple drops of up to 1.5 meters / 5 ft. onto concrete.

INDUSTRIES

Supermerkets

Restaurants

Logistics

Industries

Hospitals

Cinemas

Banks

Amusement Parks

Fashion

DESCRIPTION

The **LI102** scanner is ideal for any type of business. This device comes with a resting base, and thanks to its linear image technology, it can directly read barcodes from screens. This scanner is capable of reading up to **300 codes per second**, and its lightweight design with a firm grip enhances worker efficiency.

LED Indicator

USB Connection

Resting Base

Captures codes that are not very sharp

Reads on screens

*Specifications are subjetc to change without previous notice

2 YEARS

PRODUCT WARRANTY

SPECIFICATION		DESCRIPTION
Physical Specifications	Dimensions	95mm x 70mm x 168mm / 3.7 in x 2.8 in x 6.6 in (LxWxH)
	Weight	127.8 g / 4.5 Oz
	Color	Black
	Cable Length	1.5m / 5 ft
	Drop and shock resistance	Drops up to 1.5 meters / 5ft onto concrete.
	User Indicators	Green light successfull scanning
Performance Specifications	Scan Speed	≥300 scans/seg.
	Scan Mode	Manual Continuous
	Interface	USB
	Scan Angle	±30° (R) / ±75° (P) / ±45° (Y)
	Image Sensor	2500 Pix
	Foto Sensor	N/A
	Light Source	632nm red LED
	Scan Coverage	Code 39: 6 digits distance 4.5-10cm / 1.7 in - 4 in
	Low Contrast Printing	>25%UPC/EAN 13
Decodification Capacity	**1D:** CODE 128, EAN-13, EAN-8, UPC-E, UPC-A, ISBN, ISSN, Code11, Interleaved 2 of 5, Code39, Code93, Code32, Codebar, Matrix 2 de 5, Industrial 25, IATA25, MSI Plessey, GS1 Databar, Plessey, Febraban.	
Environment Parameters	Operating Temperature	-20°C~65°C / -4°F~149°F
	Storage Temperature	-30°C~70°C / -22°F~158°F
	Relative Humidity	5%~90% (Not condensed)
	Ambient Lighting	0~100000LUX
Electric Parameters	Voltage	DC5V±10%@138mA MAX
	Standby Power Consumption	90mA
	Operating Power Consumption	155mA

CERTIFICATIONS

CE   RoHS COMPLIANT   FC

2 YEARS

PRODUCT WARRANTY

DIMENSIONS

95 mm
3.7 in

70 mm
2.9 in

168 mm
6.6 in

OTHER SCANNERS

SAT LD101R PLUS

SAT AI402 ID OCR

COMPLEMENTARY PRODUCTS

AIO POS CI150

POS PRINTER SAT 38T

Cash Drawer SAT 119Z

*Complementary products are sold separately.