

PORTABLE PRINTER

SAT AF330



FEATURES

- USB battery charging support.
- Long-lasting battery life.
- Dual-mode Bluetooth connectivity.
- Informative OLED display.
- Print command compatibility: TSPL, EPL, ZPL, DPL, CPCL.
- Wide 1D & 2D barcode support.

DESCRIPTION:

SAT POS Solutions delivers customized point-of-sale systems designed to optimize efficiency, enhance workflows, and elevate both employee and customer experiences.

Combines sleek design, versatility, and rugged reliability for uninterrupted 24/7 operation.

Engineered for performance, the AF230 achieves print speeds of up to 100mm/s, ensuring fast and precise transactions. Its ergonomic design enhances usability, while its IP54-rated construction resists water splashes and simplifies maintenance—making it ideal for demanding retail and industrial environments.



Engineered to deliver the ideal compact printing experience with high-speed performance.

High-quality printing technology for 1D/2D barcodes and QR codes





Seamless Bluetooth connectivity (3.0 & 4.0 / DUAL BAND mode) with broad compatibility (Android, WinCE, Windows, iOS)

Extended battery life - up to 3 days in standby mode





Versatile deployment - perfect for POS billing solutions (payment terminals, stationery stores, and more)

MARKETS AND APPLICATIONS











Nightclubs









The specifications are subject to change without prior notice. Please read the instruction manual carefully to ensure proper use of the equipment.










SPECIFICATIONS		DESCRIPTION
Printing	Resolution	203 DPI
	Printing Method	Direct Thermal
	Print Speed	Up to 70 mm/s (2.7"/s)
	Maximum Print Width	72 mm (2.8")
	Maximum Print Length	1178 mm (46.4")
	Cutting Type	Manual
Paper	Paper Type	Continuous paper, black mark paper, gap label
	Paper Width	20 mm - 76 mm
	Paper Thickness	0.06 mm - 0.254 mm
	Roll Diameter	50 mm
	Paper Loading	Quick-load (Drop-in & Print)
Performance	Processor	32-bit RISC CPU
	Memory	8MB Flash / 8MB SDRAM
	Interface	USB 2.0 + Bluetooth 4.0/3.0 (Dual Mode) Optional:USB 2.0 + WiFi (802.11 b/g/n)
	Display	1.3" OLED (128×64 pixels)
	Sensors	Paper gap sensorLid open sensorBlack mark sensor.
	BUILT-IN FONTS	8 built-in alphanumeric bitmap fonts Windows® font compatibility (downloadable via software)
Fonts/Graphics /Symbols	1D Barcodes	Code 39 Full ASCII mode Code 93 Standard Code 128 UCC, Subsets A/B/C Codabar Interleaved 2 of 5 With check digit EAN/UPC EAN-8, EAN-13, UPC-4, UPC-E Others MS, Plessey, POSTNET, China POST
	2D Barcodes	PDF-417, Maxicode, DataMatrix, code QR, aztec
	Rotation	0°, 90°. 180°. 270°
	Emulation Modes	TSPL.EPL,ZPL,DPL,CPCL,ESC/POS
Reliability	Printhead Service Life	30 KM
Features	Dimensions	124mm x 108mm x 61mm (DxWxH)
	Weight	357 g.
Software	Operating System	Windows / Android / iOS
Software	SDK Support	Windows / Android / iOS
Power	Power Output	DC 9V /2A
	Battery	7.4V /2500mAh
Environmental	Operating Environment	5°C to 40°C (41°F to 104°F) 25% to 85% RH (non-condensing)
	Storage Environment	-40°C to 60°C (-40°F to 140°F) 10% to 90% RH (non-condensing)
Package contents	Package Contents	1 × AF330 Printer 1 × S8mm thermal paper roll (sample) 1 × Type-C-targer with cable 1 × Rechargeable battery 1 × Paper adjustment guide



CERTIFICATIONS & COMPLIANCE







DIAGRAMA

- 1. Paper Exit
- 2. Power Button (On/Off)
- 3. Paper Cover Latch
- 4. Display Screen
- 5. Clamshell Switch
- 6. Transparent Housing Lens
- 7. Mid-Frame
- 8. Paper Feed Button
- 9. Base
- 10. Menu Button

