



THERMAL POS PRINTER

SAT 15T2 U

Benefits

- ✓ 24/7 operation.
- ✓ Modern, compact design.
- ✓ Barcode printing.
- ✓ Versatile machine, two connection interfaces (USB/Bluetooth).
- ✓ Ideal solution for high-traffic use.
- ✓ Environmentally friendly, Energy Star certified.
- ✓ Easy paper loading.
- ✓ Manual cutter

Markets



Restaurants



Supermarkets



Payment points



Retail



Stores



Bars and nightclubs



Pharmacies



Airlines



Banking and finance

Description

SAT POS solutions, designed exclusively to fit your needs. Streamline, optimize, and effectively renew your processes, delivering the experience your employees need and customers want.

We designed our 15T2 U printers to offer the perfect combination between elegance, versatility, and reliability for your business (24/7 operation).

The 15T2 U series offers high print speed, up to 80mm/s, thanks to its patented technology. Splash- and dust-resistant, making it a perfect printer for high-traffic points of sale, all while keeping its low power consumption, energy-efficient and environmentally friendly.




Our thermal printers are designed to deliver the ideal compact experience thanks to their print speed.

High-quality print technology for 1D barcodes.



Thanks to its USB/Bluetooth connectivity, it offers broad compatibility with POS systems.

Ergonomic design made for tight spaces requiring optimal print quality; its practical design resists dust and water.



Installation flexibility. Ideal for POS billing point-of-sale solutions (payment points, stationery stores, etc...)



*Specifications are subject to change without notice

WARRANTY



SPECIFICATIONS		DESCRIPTION
Printing	Printing	Direct Thermal
	Resolution	203dpi (about 8 dots/mm)
Paper	Paper type	Thermal paper
	Paper width	58mm
	Thickness	0.05 ~ 0.1mm
	Paper loading	Easy top paper loading
	Paper cutting	Manual
	Paper roll diameter	max. 70mm dia.
	Cutter	+1,000,000 cuts
	Print width	48mm
Barcode	1D / 2D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE39
Detection	Sensors	Paper out, cover-open switch
Indicators - LED	Power	Green LED
	Error	Red LED
Cash drawer connection	Cash drawer	24V Cash drawer
	Print speed	Max. 80mm/s
Interfaces	USB	USB
	Serial / Bluetooth	1x USB, Bluetooth
Power Supply	Input	AC100V-240V
	Output	DC 9V, 2A
Environment	Operating temperature	0°C ~ 40°C, 20% ~85% RH
	Storage humidity	-20°C ~ 70°C, 5% ~95% RH
Dimensions	Unit dimensions	218*182*140mm (DxWxH)
	Weight	15 kg
Software	Driver	Windows 7/8/1, Server 2008/2012/2016, Linux, javapos, OPOS, macOS

*Specifications are subject to change without notice

Complementary products for a POS solution



AIO UNIT
SAT CI150

Screen size	15 Inches
Aspect ratio	7:3
Processor	Intel® Haswell Core i5
MTBF Life	50,000 Hours

Barcode Reader
SAT LD101R PLUS

Technology	Linear laser
Decoding	ID
Speed	300 Scans/second



Thermal Printer
SAT 38T

Print speed Max.	300mm/s
Paper Size	58mm/80mm
Paper Cutting	Partial or full