

THERMAL PRINTER

SAT 38T USE



FEATURES

- ✓ Working 24 / 7
- ✓ Energy Star certification
- ✓ Ideal solution for high-traffic environments.
- ✓ LED paper feed indicator.
- ✓ Triple communication interface.
- ✓ Watermark printing.

DESCRIPTION

SAT POS Solutions custom-designed exclusively for your needs. Streamline, optimize, and effectively renew your processes, providing the experience your employees need and your customers desire.

We design our 38T Printers to deliver the perfect combination of elegance, versatility, and reliability for your business (24/7 operation).

The 38T Series offers high printing speeds of up to 300mm/s, thanks to its patented technology that manages the print alert buzzer. It maintains low energy consumption, energy efficiency, and environmental friendliness without compromising performance.

MARKETS



Restaurants



Supermarkets



Payment Points



Retail



Stores



Bars and Nightclubs



Pharmacies



Airlines



Casinos



Thermal printers are designed to deliver the ideal compact experience thanks to their printing speed.

The 38TUSE Printer only requires one consumable (thermal paper), due to its printing method.



Its operation supports multiple communication interfaces (USB-SERIAL-NETWORK), ensuring high compatibility with POS systems.

LED indication technology for paper feed, error, and power.



Installation flexibility. Ideal for POS billing solutions (Payment points, Restaurants).



WARRANTY



SPECIFICATIONS		DESCRIPTION
Printing	Print Method	Direct Thermal
	Resolution	203dpi (about 8 dots/mm)
	Printing Speed	Max. 300mm/s
	Width	48MM/78MM
Paper	Paper Type	Thermal Paper
	Paper Size	58mm/80mm
	Paper Density	1 to 4
	Paper Roll Diameter	Up to 83mm
	Paper Loading	Easy top loading (Drop-In & Print)
	Thermal Print Head	150k
	Paper Cutting	Partial Cut
	Auto Cutter	2.0000.000 km
Barcode	Supported Codes	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93, QR, PDF 417
LED Indicators	Power	Green LED
	Paper	Red LED
	Error	Red LED
Memory	RAM	16MB
	Flash	32MB
Cash Drawer Connection	Cash Drawer	1x RJ11
Interfaces	USB	1x USB
	Serial	1x Serial
	Ethernet	1x Ethernet
Power Supply	Input	AC100V-240V, 50Hz/60Hz
	Output	DC 24V/2A
Environment	Operating Temperature	0°C/40°F -20°C/85°
	Storage Temperature	(-20°C/-4°F-60°C/140°)
	Operating Humidity	20% - 70% RH (non-condensing)
	IP Protection	IP56 (with top protector)
Dimensions	Equipment Size	197 × 145 × 146 mm (DxWxH)
	Weight	1.8 kg
Software	Drivers	Windows XP/Vista/7/8/10/11, Linux, OPOS (ESC/POS Emulation), JavaPOS, macOS, Android, iOS
	Accessories	USB cable, serial cable, paper roll, power adapter, CD, quick start guide

Dimensions



PRINTER VIDEO



Complementary products for a POS solution



All-in-One Equipment SAT CI150

Screen Size	15 inches
Aspect Ratio	7:3
Processor	Intel® Haswell Core™ i5
MTBF Life	50.000 hours

Barcode Reader SAT LD101R PLUS

Technology	Linear Laser
Decoding	1D
Speed	300 scans/second



Complementary products are sold separately.

SAT 38T

Printing Speed	Máx. 300mm/s
Paper Size	58mm/80mm
Paper Cutting	Partial or Full